

Maintenance mode

1. Nella vista utenti selezionare solo email. Copincollare in un client di posta elettronica togliendo gli indirizzi particolari.
2. Disattivare sincronizzazione su DNS e DHCP
3. In /etc/apache2/sites-enabled/indirizzi.conf commentare il resto e lasciare solo

```
Require ip 140.105.171.240/28
```

4. Riavviare apache con

```
apache2ctl reload
```

e verificare raggiungimento da fuori units

Modifica del mac address da parte di utenti non amministratori

```
root@schermo:/var/www/phpipam/app/subnets/addresses# diff address-  
modify.php.original address-modify.php  
281,282c281,283  
<             print ' <input type="text" name="mac" class="ip_addr form-  
control input-sm" placeholder="'._('MAC address').'" value="'.  
$address['mac']. '" size="30" '.$delete.'  
disabled="disabled">'.$mcast_help_block;  
<             print ' <input type="hidden" name="mac" value="'.  
$address['mac']. '">';  
---  
>             print ' <input type="text" name="mac" class="ip_addr form-  
control input-sm" placeholder="'._('MAC address').'" value="'.  
$address['mac']. '" size="30" '.$delete.'>'.$mcast_help_block;  
>             #print ' <input type="text" name="mac" class="ip_addr  
form-control input-sm" placeholder="'._('MAC address').'" value="'.  
$address['mac']. '" size="30" '.$delete.'  
disabled="disabled">'.$mcast_help_block;  
>             #print ' <input type="hidden" name="mac" value="'.  
$address['mac']. '">';
```

Popolazione del last seen con i dati di

netdisco

Crontab postgres

```
*/10 * * * * /var/lib/postgresql/aggiornalastseensuphpipam.sh >  
/var/lib/postgresql/aggiornalastseensuphpipam.log
```

```
#!/bin/bash  
pgrep -f aggiornalastseensuphpipam > /dev/null ||\  
echo "select INET_NTOA(ip_addr) from ipaddresses" | mysql -N -u phpipam -  
pHooqu8ae -D phpipam 2>/dev/null | while read ip; do psql netdisco -qtc  
"select ip,to_char(time_last,'YYYY-MM-DD HH24:MI:SS') from node_ip where  
active=TRUE and ip='$ip'"; done | sed '/^\s*/d' | awk -F'|' '{print $1,$2}'  
| awk '{print "update ipaddresses set lastSeen=#"$2,$3"# , state=2 where  
ip_addr=INET_ATON("#$1"#)";"}' | sed "s/#/\'/g" | mysql -vvvv -u phpipam -  
pHooqu8ae -D phpipam
```

From:

<https://docu.units.it/dokuwiki/> - Area dei Servizi ICT - Documentation

Permanent link:

<https://docu.units.it/dokuwiki/ipam:aggiornamento-personalizzazione>

Last update: **2024/03/19 09:25 (8 settimane fa)**

