

# Uso del modulo rlm\_attr\_filter

## attrs file

Applies to: proxy-reply packet received from a home server Decides: which attributes and/or values we allow proxy servers to pass to the NAS for this realm.

You can have only one DEFAULT entry. Only the first match is used unless the “Fall-Through” variable is set to “Yes”.

## attrs.access\_challenge file

Non usato nei sites-enabled

## attrs.pre-proxy file

Applies to: outgoing proxied accounting packets, outgoing proxied packets (e.g.: auth-reply, eap handshake, ecc... ) Decides: which attributes and/or values we allow to be sent to the home server of a realm

## attr\_filter.accounting\_response file

```
# Filter attributes from the accounting response.  
attr_filter.accounting_response  
# This configuration file is used to remove almost all of the  
attributes  
# From an Accounting-Response message. The RFC's say that an  
# Accounting-Response packet can contain only a few attributes.  
# We enforce that here.
```

## attrs.access\_reject file

```
# This configuration file is used to remove almost all of the  
attributes  
# From an Access-Reject message. The RFC's say that an Access-Reject
```

```
#       packet can contain only a few attributes. We enforce that here.
```

From:

<https://docu.units.it/dokuwiki/> - Area dei Servizi ICT - Documentation



Permanent link:

<https://docu.units.it/dokuwiki/radius:attrs.filter>

Last update: **2013/10/17 10:51 (11 anni fa)**